



LED1550-1F0

- Fiber Coupled LED
- 1550 nm
- 1.0 mW CW
- 600 µm fiber
- CE certified
- 1 Year warranty



Description

LED1550-1F0 is a fiber coupled LED, emitting at a wavelength of typically **1550 nm**, with an output power of **1.0 mW at the tip of the 600 µm fiber**. It consists of the LED unit with SMA905 connector and a 1 m 600 µm fiber, a control unit, and a separate power supply, supporting a wide input voltage range of 90-260 VAC. TTL or Analog modulation and different fibers (400, 800, 1000 µm) are optionally available. **LED1550-1F0** is RoHS compliant, CE certified, and comes with a **1 Year warranty**

Electro-Optical Characteristics (T_{CASE} = 25°C)

Parameter	Values	Unit
Wavelength	1550 ± 30	nm
Half Width	100	nm
Output Power	1.0 mW (with 600 µm fiber)	mW
Operating Mode	CW	
Fiber Core Diameter	400*, 600, 800*, 1000*	µm
Fiber Length	~ 1	m
Fiber NA	0.22	
Fiber Connector	SMA905	
Maximum Current	700	mA
Forward Voltage	1.1	V
Warm-up time	< 5	min
Operating Temperature	10 ~ 35	°C
Storage Temperature	-20 ~ 80	°C
Input Power	12 VDC, 7 A	
Power Supply	100-240	VAC
Expected Lifetime	10000	hours

* optionally available





Options

Options	Description
Modulation input	TTL or Analog modulation input

Outline Dimensions

