



LED600-3F0

- Fiber Coupled LED
- 600 nm
- 3 mW CW
- 600 µm fiber
- CE certified
- 1 Year warranty



Description

LED600-3F0 is a fiber coupled LED, emitting at a wavelength of typically **600 nm**, with an output power of **3 mW at the tip of the 600 µm fiber**. It consists of the LED unit with SM905 connector and a 1 m 600 µm fiber, a control unit, and a separate power supply, supporting a wide input voltage range of 90-260 VAC. TTL or Analog modulation and different fibers (400, 600, 800, 1000 µm) are optionally available. **LED600-3F0** is RoHS compliant, CE certified, and comes with a **1 Year warranty**

Electro-Optical Characteristics (T_{CASE} = 25°C)

Parameter	Values	Unit
Wavelength	600	nm
Half Width	64	nm
Output Power	3 mW (with 600 µm fiber)	mW
Operating Mode	CW	
Fiber Core Diameter	400*, 600 , 800*, 1000*	µm
Fiber Length	~ 1	m
Fiber NA	0.22	
Fiber Connector	SMA905	
Maximum Current	1000	mA
Forward Voltage	2.6	V
Warm-up time	< 5	min
Operating Temperature	10 ~ 35	°C
Storage Temperature	-20 ~ 80	°C
Input Power	5 VDC, 5 A	
Power Supply	100-240	VAC
Expected Lifetime	10000	hours

* optionally available





Options

Options	Description
Modulation input	TTL or Analog modulation input

Outline Dimensions

